



SARAS KİMYA

TECHNICAL DATA SHEET (TDS)

PARQUETMAX FLEX

Polyurethane Adhesive for Parquet & Wood
Technical Data Sheet

Product Description

Saras Parquetmax Flex is a solvent free, two component polyurethane based parquet adhesive.

Properties

Parquetmax Flex resists against humidity, water and most of the chemicals. It has very good filling capacity and thixotropic properties. Flex gives better result in fixing wooden to concrete than other kinds of adhesives. Parquetmax Flex is suitable to use with underfloor heating.

Application Areas

Parquetmax Flex is an adhesive for bonding parquet, laminate and all kinds of wood.

Application Instructions

The resin component A should be thoroughly stirred to incorporate any slight separation, whilst continuing stirring the contents of the hardener component B should be added. Continue stirring until a homogeneous mix is obtained. The mixed material must be used within 45 minutes of mixing at 20°C. The surface must be dry and clean. Parquetmax Flex can be applied by a trowel or a comb. On uneven or rough surfaces, use Polmax 01 Primer primer before applying adhesive. On even but clammy, dusty and unprepared surfaces, prime the surface with Polmax 01 Primer. Up to 75% moisture on damp surfaces Epomax 02 Hum Primer moisture barrier is recommended.



SARAS KİMYA SANAYİ VE TİCARET LTD. ŞTİ.



+90 850 885 51 85
+90 216 599 11 85



Egemen Sanayi Sitesi, Orta Mah.
Keban SK. No: 10 - B30 Tuzla -
İSTANBUL / TÜRKİYE



www.saraskimya.com
info@saraskimya.com



Technical Properties

Mixing Ratio	9 : 1 (By weight)
Density of mixture (20°C)	app. 2,01±0.1 gr/cm ³
Density of Comp. A (20°C)	app. 2,10±0.1 gr/cm ³
Density of Comp. B (20°C)	app. 1,22±0.05 gr/cm ³
Pot-life (23°C)	30-40 min.
Application temperature	Min 5°C
Curing (20°C and %60 relative humidity)	4 hours
Set to pedestrian traffic	24 hours
Color and odor	Crème, Odorless

Consumption

1,3 kg – 1,7 kg is used per m² (depends on the surface absorbance)

Storage

1 year under standart room conditions. Products should remain in their original, unopened packages, bearing the manufacturers name, product designation, and batch number and application precaution labels.

Packaging

10 KG Bucket (A+B)

Important Notes

Substrate must be dry, clean, and free from dust, grease and oil. Application must be done between 5°C and 30 °C.

Cautions

Harmful if swallowed. Seek immediately medical attention. Rubber gloves and safety glasses with side guards should be worn.

